

1330



Tally

Tally Dascom's 1330 flatbed serial dot matrix printer, is 24-pin, 82-column printer with USB interface as standard. The 1330 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited.

The 1330 is equipped with a linear encoder sensor to position the print head with high accuracy and intellectually detect and correct any misplaced carriage, which ensures good printing quality and significantly reduces the chances of errors in printing.

Highlights at a glance:

- Advanced 24-pin, 82-Column flatbed printer
- Up to 450 CPS speed
- Ideal for front and back office application
- Up to 7-parts copy capability
- Supports A3 portrait
- Intelligent print position tracking sensor

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1330 is ideal for counter-top printing applications such as cheques, tickets, receipts, forms and multi-part documents.

Using the long life ribbon option, the 1330 requires fewer ribbon changes, less downtime and lower running costs. With print speeds of up to 450 characters per second (cps) and flexible media handling, it keeps transactions smooth and the user happy.

The 1330 is a reliable and easy to use printer, with low running costs and a small footprint.

Configurations:

- **1330** Standard Product

1330

| | |
|--------------------------------|---|
| Print Speed | 450 cps (Fastest Draft); 300 cps (Draft), 200 cps (NLQ) at 10 cpi |
| Resolution | up to 360 x 360 dpi |
| Character Density | 10, 12, 15, 16.6, 17.1, 20, 24 cpi |
| Line Density | 1/6 inch, programmabl in 1/360 inch increments |
| Printhead Life | 400 million strokes per pin |
| Memory | up to 256 kB |
| Standard Connectivity | USB 2.0 |
| Optional Connectivity | Parallel (IEEE 1284), Serial (RS-232C) |
| Standard Emulation | Epson ESC P/2, IBM PPDS |
| Fonts | HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes |
| Consumables | Ribbon: 7 million characters |
| Standard Paper Handling | Friction and push tractor |
| Number of Copies | 1 original + 6 copies |
| Paper Type | Cut sheets, Continuous forms, multi-part forms |
| Paper Weight | 52-120 g/m ² |
| Paper Size | Width: 55 to 297 mm (Cut Sheet) |
| Physical Weight | 4,2 kg |
| Physical Size | 395 x 320 x 205 mm (W x D x H) |
| Acoustic | <57 dB(A) |
| Power Voltage | 230 V - 50/60 Hz |
| Power Consumption | 5,9 Watt Stand-By |
| Temperature | 5° to +35° C; 10% to 95% humidity |
| Workload | 6.000 pages per month |
| MTBF | 12.000 hours |
| Drivers | Windows 7/8/10 and Server 2008/2012 |

DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 355130 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.co.uk

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 