

2380 Dot Matrix Printer

High speed & Rugged for Heavy Duty Operation



- Print speeds up to 1000 cps
- Full range of automatic features to minimize user intervention
- Ideal for 'On Demand' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard
- Optional Interfaces: RS232 Serial; Coax/Twinax; Ethernet IPDS
- Compatible with a wide range of operating systems including Windows; UNIX; DOS; SAP R3 and Legacy systems

The 2365 MC and 2380 printers are rugged and powerful high speed matrix printers for heavy duty operation under the most extreme conditions. Reliable, heavy workload output is guaranteed for many years following printer purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

Fully automated operation, coupled with the 'straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems.

Available Configuration:

2380
2380 2T with additional rear tractor

- Print Speed** At 10, 12 cpi: High Speed Draft 800, 1000; Draft 667, 800; NLQ 222, 267
- Print Method** Serial Impact
- Resolution** 360 x 360 dpi
- Throughput** 625 pages per hour (ECMA 132)
- Character Density** 5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
- Line Density** 2, 3, 4, 6, 8, 12 lpi
- Printhead Life** 750 M Characters (draft)
- Standard Connectivity** Bi-directional Parallel plus Ethernet 10/100BaseT with 128kb buffer
- Optional Connectivity** RS232 Serial, Adapters, Twinax/Coax, Ethernet IPDS
- Standard Emulation** IBM® Proprinter, Epson® LQ (ESC P/2), Genicom ANSI, MTPL + Barcode/LCP
- Optional Emulation** PCL3 (rugged writer)
- Fonts** HS Draft, Draft, Copy Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, Kix/Royal, OCR A, OCR B, 22 Bar Codes & scaleable LCP fonts.
- Consumables** 20 M Character Ribbon
- Std Paper Handling** Push tractor with paper parking and AGA; 2nd rear push tractor - 2380-2T only
- Opt'l Paper Handling** 2nd front tractor (user installable), paper pedestal, paper basket
- Number of Copies** Original + 5 (6-part forms); original +1 (2-part forms) for rear tractor of 2380-2T
- Paper Type** Continuous forms
- Paper Weight** 60-120gsm
- Paper Size** 100 to 420mm wide
- Physical Weight** 19Kg
- PhysicalSize** (HxWxD): 280x623x432mm
- Power Voltage** 120V/230V
- Power Consumption** 70 Watts printing, max 18 Watts in sleep mode
- Compliance** Energy Star qualified, Ozone-free. RoHS, Microsoft, ISO-compliant
- Workload** Up to 50,000 pages per month
- Reliability MTBF** 12,500 hours @ 25% duty cycle
- Reliability MTTR** 30 minutes
- Drivers** Windows 9x/ME, 2000, 2003 Server, XP, Vista and SAP
- Temperature** +10°C to +35°C
- Humidity** 20% to 80%
- Acoustic** 59dBA (ISO 7779)
- Warranty** 1 year on site next business day (extended warranty is 1 + 2 years)
- Options** 2nd front tractor (user installable), paper pedestal, paper basket
- Note** For OCR applications it is recommended that your readers are tested with print samples supplied by TallyGenicom prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operating conditions.

Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice. Copyright © 2008 TallyGenicom, L.P.

Printed Date: 08/03/2008



Rutherford Road, Basingstoke,
Hampshire RG24 8PD
Tel: UK 0800 652 4557
International: +44 1256 481 521
Fax: UK 0870 872 2889
www.tallygenicom.co.uk