

## 7106



Tally Dascom's 7106 direct thermal printer offers reliability, precision and performance in desktop size, where space is limited.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media loading. The clear panel enable simple and effective operation making it very simple to use.

The mechanism uses an all-metal construction ensuring reliable operation, a must for all industrial environments.

### Highlights at a glance:

- Space-Saving Design Concept
- Easy and Quick media loading
- Serial and USB Standard
- Supports Zebra® and Datamax® emulation
- Optional Cutter and Peeler
- Internal 5 inch (125mm) media capacity

The 7106 offers a wide range of features and options usually only found on high performance machines.

For example, it has an internal power supply providing the most reliable operation and avoiding problems usually associated with external power supplies.

The 7106 is easily integrated into existing systems, internal Ethernet interface is also available. In addition to this, the 7106 is also available with options such as a cutter and a peeler to meet industry requirements.

### Configurations:

- **7106** Standard Product

## 7106

|                              |   |
|------------------------------|---|
| <b>Print Speed</b>           | 6 ips (152 mm/sec)  |
| <b>Print Width</b>           | 4.10 inches (104.1 mm)  |
| <b>Print Method</b>          | Direct Transfer   |
| <b>Print Length</b>          | 0.25" to 32" (6.35 mm to 812,8 mm)  |
| <b>Resolution</b>            | 203 dpi:  |
| <b>Font Bitmapped</b>        | 7 styles, True Type   |
| <b>Printhead Life</b>        | 50 km or 6 months   |
| <b>Memory</b>                | 16 Mb SDRAM; 4 Mb Flash   |
| <b>Connectivity Standard</b> | Serial (RS-232C), USB (Version 1.1)   |
| <b>Connectivity Optional</b> | Ethernet LAN (10/100 BaseT), Parallel (IEEE-1284)   |
| <b>Emulation</b>             | Auto-switching Zebra ZPL-II and Datamax I-Class, DMX400, Prodigy Plus   |
| <b>Consumables</b>           | Thermal direct paper and label  |
| <b>Media Width</b>           | 0.77" to 4.65" (19.6 mm to 118.1 mm)  |
| <b>Media Length</b>          | 0.25" to 32" (6.35 mm to 812,8 mm)  |
| <b>Roll Diameter</b>         | Internally: 5" (127 mm) . Externally 8" (203 mm) with optional holder<br>Core size 1" - 3" (25 mm to 76 mm).  |
| <b>Indexing</b>              | Fully adjustable rear sensor  |
| <b>Barcodes</b>              | Code11, Code39, Code93, Code128, I2of5, S2of5, EAN8, EAN13, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC A/E, POSTNET, Planet, Code49, PDF417, CODABLOCK, Maxicode, DataMatrix, QR Code, RSS, TLC39 |
| <b>Physical Weigth</b>       | 3.6 kg  |
| <b>Physical Size</b>         | 183 x 231 x 289 mm (H x W x D)  |
| <b>Power Voltage</b>         | 220-240 V AC, 50-60Hz   |
| <b>Power Consumption</b>     | max 12,9W in Standby, 196W in Operating   |
| <b>Drivers</b>               | Windows XP, 2003, Vista, Win 7 (32/64 Bit)  |
| <b>Temperature</b>           | +5°C to +35°C   |
| <b>Humidity</b>              | 30% to 80% (not condensing)   |
| <b>Acoustic (ISO 7779)</b>   | <55 dB(A)   |
| <b>Options</b>               | Auto Cutter, Peeler, Parallel and LAN Interfaces  |
| <b>Note</b>                  | Accessories Supplied: Head cleaning pen, Start-Up Guide,<br>CD including: Manuals, Drivers and EasyConfig Too   |

### DASCOM Europe GmbH

Europaring F15 301,  
A-2345 Brunn a. Gebirge  
Tel: +43 1 2360 170 10 – Fax: +43 1 2360 170 15  
info@dascom.com – www.dascom.com

### DASCOM GB Limited

Hart House, Priestley Road  
Basingstoke, Hampshire RG24 9PU  
Tel: +44 1256 481481 – Fax: +44 1256 481400  
info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 