

## T2265+



*Tally*

The T2265+ is undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in his respective speed segment. It is not just sprinter; reliable, heavy workload output is guaranteed for the many years following its purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

### Highlights at a glance:

- Print speeds **up to 900 cps**
- **Full range of automatic features** minimising operator intervention
- Straight through paper path for easy forms loading
- **Parallel and Ethernet (10/100BaseT) standard.**
- **Straight through paper path** for easy forms loading
- Compatible with a **wide range of operating systems**

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

The product is well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2265+ is the first high speed matrix printer to incorporate Ethernet on-board.

### Configurations:

- **T2265+** Standard Product
- **T2265+ IGP** with IGP/PJL Support

## T2265+

<b>Print Speed</b>	900 cps (Fastest Draft); 700 cps (Draft), 200 cps (NLQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	610 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	500 million characters
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and Ethernet 10/100BaseT
<b>Optional Connectivity</b>	Serial RS232, Ethernet Multiprotocol, Ethernet with SCS or IPDS support, Coax with SCS or IPDS support, Twinax with SCS or IPDS support
<b>Standard Emulation</b>	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP <b>IGP Version:</b> IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
<b>Optional Emulation</b>	ECMA 9014, MT460D, MT50
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and large character printing
<b>Consumables</b>	Ribbon: 20 million characters
<b>Standard Paper Handling</b>	Push tractor and friction, continuous paper with straight paper path, cut sheet front insertion, tear off and park position
<b>Optional Paper Handling</b>	Additional push tractor (front), Automatic sheet feeder rear (2x 190 sheets) or front (100 sheets), Automatic cutting device
<b>Number of Copies</b>	Push tractor front: 1 original + 5 copies; Cut sheet: 1 original + 5 copies
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 76 to 420 mm; Length: 76 to 559 mm
<b>Physical Weight</b>	19 kg
<b>Physical Size</b>	624 x 432 x 280 mm (W x D x H)
<b>Acoustic</b>	55 dB(A)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	65 Watt Printing
<b>Temperature</b>	+10° to +35° C; 20% to 80% humidity
<b>Workload</b>	40.000 pages per month
<b>MTBF</b>	10.000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7 and Server 2003/2008; SAP

### DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 481481 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 