

T2280+



Tally

The T2280+ is undoubtedly at the pinnacle of serial impact printing, representing the peak of performance in his respective speed segment. It is not just sprinter; reliable, heavy workload output is guaranteed for the many years following its purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Highlights at a glance:

- Print speeds **up to 1.000 cps**
- **Full range of automatic features** minimising operator intervention
- Straight through paper path for easy forms loading
- **Parallel and Ethernet (10/100BaseT) standard.**
- **Straight through paper path** for easy forms loading
- Compatible with a **wide range of operating systems**

Fully automatic operation instills operator confidence and virtually eliminates errors caused by poor user intervention. Front feed provides all the benefits of easy forms installation, coupled with reliable paper transport.

The product is well matched to Microsoft Windows applications, and entirely suited to other host operating environments, including legacy systems. The T2280+ is the first high speed matrix printer to incorporate Ethernet on-board.

Configurations:

- **T2280+** Standard Product
- **T2280+ IGP** with IGP/PJL Support
- **T2280+ 2T** with additional tractor

T2280+

Print Speed	1.000 cps (Fastest Draft); 800 cps (Draft), 222 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	680 pages per hour
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million characters
Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/100BaseT
Optional Connectivity	Serial RS232, Ethernet Multiprotocol, Ethernet with SCS or IPDS support, Coax with SCS or IPDS support, Twinax with SCS or IPDS support
Standard Emulation	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
Optional Emulation	ECMA 9014, MT460D, MT50
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and large character printing
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor and friction, continuous paper with straight paper path, cut sheet front insertion, tear off and park position
Optional Paper Handling	Additional push tractor (front), additional push tractor (rear, only T2280-2T) Automatic sheet feeder rear (2x 190 sheets) or front (100 sheets), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 5 copies; Push tractor rear: 1 original + 3 copies; Cut sheet: 1 original + 5 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 420 mm; Length: 76 to 559 mm
Physical Weight	19 kg
Physical Size	624 x 432 x 280 mm (W x D x H)
Acoustic	57 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	75 Watt Printing
Temperature	+10° to +35° C; 20% to 80% humidity
Workload	50.000 pages per month
MTBF	10.000 hours
Drivers	Windows 2000/XP/Vista/7 and Server 2003/2008; SAP

DASCOM GB Limited

Hart House, Priestley Road

Basingstoke, Hampshire RG24 9PU

Tel: +44 1256 481481 – Fax: +44 1256 481400

info.gb@dascom.com – www.dascom.com

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS